



Lane Group	SEL	SER	NEL	NET	SWT	SWR
Lane Configurations		↖			↗	↗
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Turning Speed (k/h)	25	15	25			15
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00
Frt		0.865				0.850
Flt Protected						
Satd. Flow (prot)	0	1611	0	0	1863	1583
Flt Permitted						
Satd. Flow (perm)	0	1611	0	0	1863	1583
Headway Factor	1.00	1.00	1.00	1.00	1.00	1.00
Link Speed (k/h)	60			60	60	
Link Distance (m)	421.1			262.4	351.8	
Travel Time (s)	25.3			15.7	21.1	
Volume (vph)	0	83	0	0	1731	115
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	0	90	0	0	1882	125
Lane Group Flow (vph)	0	90	0	0	1882	125
Sign Control	Stop			Stop	Stop	

Intersection Summary	
Area Type:	Other
Control Type:	Unsignalized
Intersection Capacity Utilization	102,9% ICU Level of Service G
Analysis Period (min)	15