



Lane Group	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations	↑			↑	↘	↗
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Turning Speed (k/h)		15	25		25	15
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00
Frt						0.850
Flt Protected				0.995	0.950	
Satd. Flow (prot)	1863	0	0	1853	1770	1583
Flt Permitted				0.995	0.950	
Satd. Flow (perm)	1863	0	0	1853	1770	1583
Headway Factor	1.00	1.00	1.00	1.00	1.00	1.00
Link Speed (k/h)	50			50	50	
Link Distance (m)	516.4			671.2	430.7	
Travel Time (s)	37.2			48.3	31.0	
Volume (vph)	177	0	20	191	160	114
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	192	0	22	208	174	124
Lane Group Flow (vph)	192	0	0	230	174	124
Sign Control	Yield			Yield	Yield	

Intersection Summary	
Area Type:	Other
Control Type:	Roundabout
Intersection Capacity Utilization	39,3% ICU Level of Service A
Analysis Period (min)	15